



PATENT ABSTRACTS OF JAPAN

(11) Publication number: **2003060604 A**(43) Date of publication of application: **28.02.03**(51) Int. Cl. **H04J 11/00**(21) Application number: **2001248408**(22) Date of filing: **15.08.01**(71) Applicant: **NIPPON TELEGR & TELEPH
CORP <NTT>**(72) Inventor:
**ASAI YUSUKE
UMEHIRA MASAHIRO
SUGIYAMA TAKATOSHI
KUROSAKI SATOSHI****(54) OFDM SIGNAL TRANSMISSION APPARATUS
AND OFDM SIGNAL RECEPTION APPARATUS**


COPYRIGHT: (C)2003 JPO

図1に示す実施形態の構成図

(57) Abstract:

PROBLEM TO BE SOLVED: To improve frequency utilization efficiency by composing an MIMO channel by a plurality of transmission/reception antennas for an OFDM signal transmission apparatus that is used in wideband mobile communication or the like.

SOLUTION: A transmission subcarrier pilot matrix generator, and transmission pilot signal configuration equipment are arranged as a pilot signal generator in the OFDM signal transmission apparatus. The transmission subcarrier pilot matrix generator generates a matrix other than a single matrix where a determinant does not become zero and a matrix of the complex multiples of the single matrix with a transmission pilot signal p^{1mn} at the m -th symbol that is transmitted by the n -th antenna in the i -th subcarrier as constituents in the m column n row. The transmission pilot signal configuration equipment inputs a constituent at m column n row into a multiplexing circuit from all P as transmission pilot signal constituents (p^{1mn} , p^{2mn} , ..., p^{Pmn}) at the m -th symbol in the n -th antenna.

**BEST AVAILABLE COPY**